

RECEIVED
CENTRAL FAX CENTER

003

Serial No. 09/954,621

AUG 10 2006

PATENT

New Atty Docket No.: 67134-5040

Amendments to the Claims

This Listing of Claims replaces all prior versions, and listings, of claims in this application.

1-18. (Cancelled).

19. (Currently Amended) A label sheet construction, comprising:

a liner sheet;

a facestock sheet adhered to the liner sheet;

at least one first cut line through the facestock sheet but not the liner sheet to form an entire perimeter of a facestock sheet first label releasably adhered to the liner sheet;

at least one second cut line through the facestock sheet but not the liner sheet to form a facestock sheet second label releasably adhered to the liner sheet;

the second label being spaced from the first label and separated therefrom by a non-label waste portion of the facestock sheet;

~~a weakened line segment~~ an elongate continuous die cut line in the facestock sheet outside of, and extending ~~at least substantially~~ from the first label to the second label;

the elongate continuous die cut line is a portion of a fold line which passes through the first and second labels;

the facestock sheet being constructed and adapted to be and capable of being bent back on the ~~weakened line segment~~ fold line to thereby separate the liner sheet away from a portion of the first label whereby the label portion can be grasped ~~by a user~~ and the first label can be peeled off of the liner sheet; and

~~the weakened line segment~~ elongate continuous die cut line extending through the facestock sheet but not through the liner sheet.

20. (Cancelled).

Serial No. 09/954,621

PATENT

New Atty Docket No.: 67134-5040

21. (Currently Amended) The construction of claim ~~[[20]]~~ 19 wherein the elongate continuous die cut line engages at opposite ends thereof the first and second cut lines, and the cut line and the first and second cut lines comprise a continuous die cut line.

22. (Currently Amended) The construction of claim 19 further comprising at least one third cut line through the facestock sheet but not the liner sheet to form a facestock sheet third label releasably adhered to the liner sheet, the first, second and third labels being aligned in a row on the facestock sheet, the ~~weakened line segment~~ elongate continuous die cut line defining a first elongate continuous die cut line segment, and a ~~weakened line segment~~ second elongate continuous die cut line extending between the second and third labels, the second elongate continuous die cut line lying on the fold line.

23. (Currently Amended) The construction of claim 22 wherein ~~the first and second segments are in the same line, and~~ the construction has a structure such that when the facestock sheet is bent back on the first segment first elongate continuous die cut line the facestock sheet is also bent back on the second ~~segment~~ elongate continuous die cut line to thereby separate the liner sheet away from a portion of the second label whereby the label portion of the second label can be grasped ~~by a user~~ and the second label peeled off of the liner sheet.

24. (Currently Amended) The construction of claim 19 wherein the first label has first and second parallel ends and the first ~~line segment~~ elongate continuous die cut line is parallel to and spaced between the parallel ends.

25. (Currently Amended) The construction of claim 19 further comprising a second ~~weakened line segment~~ elongate continuous die cut line which extends between the first label and an edge of the facestock sheet, the second elongate continuous die cut line lying on the fold line.

26. (Previously Presented) The construction of claim 19 wherein the first and second labels are both rectangularly shaped.

Serial No. 09/954,621

PATENT
New Atty Docket No.: 67134-5040

27. (Previously Presented) The construction of claim 19 wherein the first and second labels are both circularly shaped.

28. (Previously Presented) The construction of claim 19 wherein the facestock sheet includes a plurality of labels arranged in a multi-column, multi-row array, and the plurality of labels includes the first label and the second label.

29. (Previously Presented) The construction of claim 19 further comprising the liner sheet having a release coating, and adhesive between the facestock sheet and the release coating.

30-43 (Cancelled).

44. (Currently Amended) A label sheet construction, comprising:

a liner sheet;

a facestock sheet adhered to the liner sheet;

at least one cut line through the facestock sheet but not the liner sheet to form a facestock sheet label releasably adhered to the liner sheet and surrounded by a non-label waste portion of the facestock sheet;

a first weakened line segment in the non-label waste portion of the facestock sheet ~~on one side of the label~~, adjacent to the label and outside of and spaced a distance from the label by a first short section of uncut material; and

a second weakened line segment ~~on an opposite side of the label~~, adjacent to the label and outside of and spaced a distance from the label by a second short section of uncut material, the second weakened line segment being in the non-label waste portion of the facestock sheet, the line segments lying in the same line and with the label positioned between them, the same line extending at least substantially from a first side edge of the sheet to ~~an opposite~~ a second side edge of the sheet, the same line passing through ~~a portion of the label~~;

the same line being a weakened fold line of the construction;

the facestock sheet being adapted to be and capable of being bent back on the ~~[[same]]~~ weakened fold line to thereby separate the liner sheet away from a portion of

Serial No. 09/954,621

PATENT
New Atty Docket No.: 67134-5040

the label such that the label portion ~~is adapted to be and capable of being~~ can be grasped ~~by a user~~ and the grasped label can be peeled off of the liner sheet; and

wherein the first and second weakened line segment ~~extends through the~~ facestock sheet to segments do not pass through the liner sheet.

45-46 (Cancelled).

47. (Previously Presented) The construction of claim 44 wherein the first weakened line segment has a discontinuous spacing between adjacent labels.

48. (Previously Presented) The construction of claim 44 wherein the liner sheet has a silicone coating, and a layer of adhesive is sandwiched between the facestock sheet and the silicone coating.

49. (Previously Presented) The construction of claim 44 wherein the label has a burst configuration with alternating long and short points.

50. (Currently Amended) A label sheet construction, comprising:
a liner sheet;
a facestock sheet adhered to the liner sheet;
at least one cut line through the facestock sheet but not the liner sheet to form a facestock sheet label releasably adhered to the liner sheet;
the label being surrounded by a non-label waste portion of the facestock sheet;
a first weakened line segment in the non-label waste portion of the facestock sheet ~~on one side of the label~~ and a second weakened line segment ~~on an opposite side of the label~~ and in the non-label waste portion of the facestock sheet, the line segments lying in the same line, the same line extending at least substantially from a first side edge of the sheet to ~~an opposite~~ a second side edge of the sheet, the same line passing through ~~a portion of the label~~;
the same line being a weakened fold line of the construction;
the label being positioned between the first and second weakened line segments;

Serial No. 09/954,621

PATENT
New Atty Docket No.: 67134-5040

the facestock sheet being adapted to be and capable of being bent back on the ~~[[same]]~~ weakened fold line to thereby separate the liner sheet away from a portion of the label such that the label portion is adapted to be and capable of being grasped by a user and the label peeled off of the liner sheet;

~~the line segments are spaced from and do not engage the label and are each spaced from the label by a short section of uncut material;~~

~~wherein the first weakened line segment ~~[[is]]~~ being ~~[[a]]~~ an elongate continuous die cut line through the facestock sheet to but not through the liner sheet~~[[; and]]~~.~~

~~wherein an end of the first weakened line segment closest to the label is spaced a distance therefrom by a short section of uncut material.~~

51. (Cancelled).

52. (Currently Amended) The construction of claim 50 wherein the second weakened line segment is ~~[[a]]~~ an elongate continuous die cut line through the facestock sheet to the liner sheet.

53. (Cancelled).

54. (Previously Presented) The construction of claim 50 wherein the first weakened line segment has a discontinuous spacing between adjacent labels.

55. (Previously Presented) The construction of claim 50 wherein the liner sheet has a silicone coating, and a layer of adhesive is sandwiched between the facestock sheet and the silicone coating.

56. (Previously Presented) The construction of claim 50 wherein the label has a burst configuration with alternating long and short points.

57. (Currently Amended) A label sheet construction, comprising:
a liner sheet;
a facestock sheet adhered to the liner sheet;

Serial No. 09/954,621

PATENT

New Atty Docket No.: 67134-5040

at least one cut line through the facestock sheet but not the liner sheet to form a facestock sheet label releasably adhered to the liner sheet;

the label being surrounded by a non-label waste portion of the facestock sheet;

a first weakened line segment in the non-label waste portion of the facestock sheet on one side of the label and outside of the label and a second weakened line segment on an opposite side of the label and outside of the label, the second weakened line segment being in the non-label waste portion of the facestock sheet, the line segments lying in the same line, the same line extending at least substantially from a first side edge of the sheet to ~~an opposite~~ a second side edge of the sheet, the same line passing through a portion of the label;

the same line defining a first weakened fold line;

a third weakened line segment in the facestock sheet on one side of the label and outside of the label and a fourth weakened line segment on an opposite side of the label and outside of the label, the second and third weakened line segments being in the non-label waste portion, the third and fourth line segments lying in the same line which defines a second fold line, the second fold line extending at least substantially from a first side edge of the sheet to ~~an opposite~~ a second side edge of the sheet, the second line passing through a portion of the label closer to a center of the label than the first fold line;

the second weakened fold line being spaced an offset distance from and generally parallel to the first fold line; and

the facestock sheet being constructed and adapted to be and capable of being bent back on the first and second fold lines to ~~thereby~~ pull the liner sheet away from a portion of the label whereby the label portion can to be grasped ~~by a user~~ and the label can be peeled off of the liner sheet.

58. (Currently Amended) The construction of claim 57 wherein weakened portions of the first fold line are the same length as those of the second fold line.

59. (Previously Presented) The construction of claim 57 wherein at least one of the first and second line segments has an unweakened portion.

Serial No. 09/954,621

PATENT
New Atty Docket No.: 67134-5040

60. (Previously Presented) The construction of claim 59 wherein each of the weakened line segments is a cut line segment through the facestock sheet.

61. (Currently Amended) The construction of claim 57 wherein the first and second fold lines have the same folding force.

62. (Previously Presented) The construction of claim 61 wherein the weakened line segments are die cut lines.

63. (Previously Presented) The construction of claim 57 wherein the label has a burst configuration.

64. (Previously Presented) The construction of claim 63 wherein the burst configuration has evenly spaced, peripheral alternating long and short points.

65. (Currently Amended) A label sheet construction, comprising:
a liner sheet;
a facestock sheet adhered to the liner sheet;
at least one cut line through the facestock sheet but not the liner sheet to form a facestock sheet label releasably adhered to the liner sheet;
a first weakened line segment in the facestock sheet on one side of the label and a second weakened line segment on an opposite side of the label, the line segments lying in the same ~~imaginary~~ line, the same ~~imaginary~~ line extending at least substantially from a first side edge of the sheet to an ~~opposite~~ a second side edge of the sheet, an ~~imaginary~~ a line portion of the same ~~imaginary~~ line passing through a ~~portion~~ of the label from one side thereof to the other, the ~~imaginary~~ line portion not being a weakened line portion;
the same line being a weakened fold line of the construction;
the facestock sheet being constructed and adapted to be and capable of being bent back on the ~~[[same]]~~ weakened fold line to thereby separate the liner sheet away from a portion of the label such that the label portion can be grasped ~~by a user~~ and the label can be peeled off of the liner sheet; and

Serial No. 09/954,621

PATENT
New Atty Docket No.: 67134-5040

the weakened line segments do not penetrate into the liner sheet.

66. (Previously Presented) The construction of claim 65 wherein the label has a burst configuration with alternating long and short points.

67. (Currently Amended) A label sheet construction, comprising:

a liner sheet;

a facestock sheet adhered to the liner sheet;

at least one cut line through the facestock sheet but not the liner sheet to form a facestock sheet label releasably adhered to the liner sheet;

a first weakened line segment in the facestock sheet on one side of the label and a second weakened line segment in the facestock sheet on an opposite side of the label, the line segments lying in the same ~~imaginary~~ line, the same ~~imaginary~~ line extending at least substantially from a first side edge of the facestock sheet to an ~~opposite a~~ second side edge of the facestock sheet, the same ~~imaginary~~ line passing through a portion of the label;

the same line being a weakened fold line of the construction:

the facestock sheet being constructed and adapted to be bent and ~~[[is]]~~ being capable of being bent back on the ~~[[same]]~~ weakened fold line to ~~thereby~~ separate the liner sheet away from a portion of the label such that the label portion can be grasped ~~by a user~~ and the label can be peeled off of the liner sheet;

the label being positioned within a perimeter of the facestock sheet and spaced a distance inward of all side and end edges of the perimeter and spaced therefrom by non-label waste portions of the facestock sheet; and

the liner sheet having no cut or weakened lines directly beneath the label.

68. (Previously Presented) The construction of claim 67 wherein the label has a burst configuration with alternating long and short points.

69. (Currently Amended) A label sheet construction, comprising:

a liner sheet;

a facestock sheet adhered to the liner sheet;

Serial No. 09/954,621

PATENT
New Atty Docket No.: 67134-5040

at least one cut line through the facestock sheet but not the liner sheet to form a facestock sheet label releasably adhered to the liner sheet;

a first weakened line segment in the facestock sheet on one side of the label and a second weakened line segment in the facestock sheet on an opposite side of the label, the line segments lying in the same line, the same line extending at least substantially from a first side edge of the sheet to an opposite a second side edge of the sheet, the same line passing through a portion of the label;

the same line being a weakened fold line of the construction;

the line segments do not penetrate into the liner sheet;

~~the facestock sheet being adapted to be and capable of being~~ construction being structured such that the facestock sheet can be bent back on the ~~[[same]]~~ weakened fold line to thereby separate the liner sheet away from a portion of the label such that the label portion is ~~adapted to be~~ can be grasped by a user and the label can be peeled off of the liner sheet; and

the at least one cut line defining at least one non-label, facestock waste portion outside of the label, and the line segments being positioned on the at least one non-label facestock waste portion and not on the label.

70. (Previously Presented) The construction of claim 69 wherein the label has a burst configuration with alternating short and long points.

71. (Previously Presented) The construction of claim 69 wherein the facestock sheet label defines a first label, and further comprising at least one cut line through the facestock sheet but not the liner sheet to form a facestock sheet second label releasably adhered to the liner sheet, the second label being spaced from the first label.

72. (Previously Presented) The construction of claim 71 wherein the at least one non-label facestock waste portion comprises a continuous waste matrix surrounding the first and second labels.

73. (Currently Amended) A label sheet construction, comprising:
a liner sheet;

Serial No. 09/954,621

PATENT

New Atty Docket No.: 67134-5040

a facestock sheet adhered to the liner sheet with adhesive;
the facestock sheet including a line of facestock sheet labels;
the facestock sheet including a weakened fold line which passes through the labels;

the facestock sheet being constructed and adapted to be and capable of being bent back on the weakened fold line to ~~thereby~~ separate the liner sheet away from portions of the labels whereby the label portions can be individually grasped ~~by a user~~ and the labels can be individually peeled off of the liner sheet;

~~wherein~~ the weakened fold line ~~[[is]]~~ including a die cut line through the facestock sheet but not penetrating the liner sheet; and

~~wherein~~ the adhesive ~~[[coats]]~~ coating the entireties of all bottom surfaces of all of the labels.

74. (Previously Presented) The construction of claim 73 wherein the labels each have a burst configuration with alternating long and short points.

75. (Currently Amended) A label sheet construction, comprising:

a liner sheet;

a facestock sheet adhered to the liner sheet;

the facestock sheet including a line of facestock sheet labels;

the labels being spaced from one another with non-label ~~facestock sheet~~ facestock sheet waste material between the labels;

the facestock sheet including a weakened fold line which passes through the labels; ~~[[and]]~~

the facestock sheet being adapted to be and capable of being bent back on the weakened fold line to ~~thereby~~ separate the liner sheet ~~[[away]]~~ from ~~portions~~ a portion of each of the labels whereby such that the label portions ~~are adapted to be and capable of being~~ can be individually grasped ~~by a user~~ and the labels can be individually peeled off of the liner sheet and away from surrounding non-label waste portions of the facestock sheet; and

Serial No. 09/954,621

PATENT

New Atty Docket No.: 67134-5040

~~wherein~~ the weakened fold line ~~includes~~ including die cut line segments in the non-label facestock sheet waste material, ~~and spaced from the labels by short sections of uncut material and~~ defining a line which passes through the labels and not passing through the liner sheet.

76. (Cancelled).

77. (Currently Amended) A label sheet construction, comprising:

a liner sheet;

a facestock sheet adhered to the liner sheet with adhesive;

the facestock sheet including a first line of spaced facestock sheet first labels and a second line of spaced facestock sheet second labels;

each of the labels being defined by weakened lines through the facestock sheet;the second line of spaced facestock sheet second labels being spaced from and parallel to the first line of spaced facestock sheet first labels;the facestock sheet including a weakened fold line which passes through the first labels;the facestock sheet being adapted to be and capable of being bent back on the weakened fold line to ~~thereby~~ separate the liner sheet away from portions of the first labels whereby the label portions are adapted to be and are capable of being individually grasped ~~by a user~~ and the first labels can be individually peeled off of the liner sheet;~~wherein the weakened fold line does not penetrate~~ not penetrating through the liner sheet; and~~wherein the adhesive~~ coating the entireties of all bottom surfaces of all of the labels.

78. (Previously Presented) The construction of claim 77 wherein each of the labels has a burst configuration with alternating long and short points.

Serial No. 09/954,621

PATENT
New Atty Docket No.: 67134-5040

79. (Previously Presented) The construction of claim 77 wherein the facestock sheet includes at least one facestock non-label waste portion, the weakened fold line being on the facestock non-label waste portion and not on the first labels.

80. (Previously Presented) The construction of claim 77 wherein centerpoints of the first labels define a line and the fold line is spaced from and parallel to the line.

81. (Previously Presented) The construction of claim 77 wherein the liner sheet has a silicone coating, and a layer of the adhesive is sandwiched between the facestock sheet and the silicone coating.

82-83 (Cancelled).

84. (Currently Amended) A label sheet construction, comprising:

a liner sheet;

a facestock sheet adhered to the liner sheet;

at least one first cut line through the facestock sheet but not the liner sheet to form a facestock sheet first label releasably adhered to the liner sheet;

at least one second cut line through the facestock sheet but not the liner sheet to form a facestock sheet second label releasably adhered to the liner sheet;

a first weakened line ~~[[first]]~~ segment in the facestock sheet outside of, and extending at least substantially from the first label to the second label;

the facestock sheet being constructed, dimensioned and adapted to be and capable of being manually bent back on the first weakened line ~~[[first]]~~ segment ~~by a user to thereby~~ separate the liner sheet away from a portion of the first label whereby the label portion is constructed, dimensioned and adapted to be and capable of being can be grasped ~~by the user~~ and the grasped first label can be manually peeled off of the liner sheet ~~by the user~~ in a direction perpendicular to the first weakened line segment;

at least one third cut line through the facestock sheet but not the liner sheet to form a facestock sheet third label releasably adhered to the liner sheet;

the first, second and third labels being aligned in a row on the facestock sheet;

Serial No. 09/954,621

PATENT
New Atty Docket No.: 67134-5040

a second weakened line ~~second~~ segment in the facestock sheet and extending between the second and third labels;

wherein the first and second weakened line segments ~~[[are]]~~ lying in the same line, the same line being a weakened fold line of the construction; [[and]]

the construction being structured such that when the facestock sheet is manually bent back on the first weakened line segment ~~[[it]]~~ the facestock sheet is also bent back on the second weakened line segment to thereby separate the liner sheet away from a portion of the second label whereby the label portion of the second label is ~~constructed, dimensioned and adapted to be and capable of being~~ can be grasped by the user and the grasped second label can be manually peeled off of the liner sheet ~~by the user~~ in a direction perpendicular to the second weakened line segment;

centerpoints of the first, second and third labels defining a centerpoint line; and

the ~~[[same]]~~ weakened fold line being spaced an offset distance from and parallel to the centerpoint line and passing through the first and second labels.

85. (Currently Amended) The construction of claim 84 further comprising a weakened line segment in the facestock sheet and extending ~~which extends~~ between the first label and an edge of the facestock sheet.

86. (Previously Presented) The construction of claim 84 wherein each of the labels has a burst configuration with alternating long and short points.

87. (Previously Presented) The construction of claim 84 wherein the facestock sheet includes a plurality of additional labels arranged in a line parallel to the same line.

88. (Previously Presented) The construction of claim 84 further comprising the liner sheet having a release coating, and adhesive sandwiched between the facestock sheet and the release coating.

89. (Currently Amended) A label sheet construction, comprising:
a liner sheet;
a facestock sheet adhered to the liner sheet with adhesive;

Serial No. 09/954,621

PATENT

New Atty Docket No.: 67134-5040

at least one first cut line through the facestock sheet but not the liner sheet to form a facestock sheet first label releasably adhered to the liner sheet;

at least one second cut line through the facestock sheet but not the liner sheet to form a facestock sheet second label releasably adhered to the liner sheet;

a weakened line segment in the facestock sheet outside of and extending at least substantially from the first label to the second label;

the weakened line segment defining a weakened fold line;

the facestock sheet being adapted to be and capable of being manually bent back on the ~~weakened line segment~~ weakened fold line by a user to thereby separate the liner sheet away from a portion of the first label whereby the label portion is ~~constructed, dimensioned and adapted to be and capable of being~~ can be grasped by the user and the grasped first label peeled off of the liner sheet ~~by the user~~ in a direction perpendicular to the weakened line segment;

at least one third cut line through the facestock sheet but not the liner sheet to form a facestock sheet third label releasably adhered to the liner sheet;

centerpoints of the first and second labels defining a first centerpoint line;

~~the third label being offset a distance from the centerpoint line;~~

~~the centerpoint line defining a first centerpoint line;~~

at least one fourth cut line through the facestock sheet but not the liner sheet to form a facestock sheet fourth label releasably adhered to the liner sheet;

centerpoints of the third and fourth labels defining a second centerpoint line;

the second centerpoint line is spaced from and parallel to the first centerpoint line; and

the adhesive coating the entire bottom surfaces of the first, second, ~~[[and]]~~ third and fourth labels.

90. (Cancelled).

91. (Previously Presented) The construction of claim 90 wherein each of the labels has a burst configuration with alternating long and short points.

92. (Currently Amended) A label sheet construction, comprising:

Serial No. 09/954,621

PATENT

New Atty Docket No.: 67134-5040

a liner sheet;
a facestock sheet adhered to the liner sheet;
the facestock sheet including a first line of spaced facestock sheet first labels and a second line of spaced facestock sheet second labels;
the second line of spaced facestock sheet second labels being spaced from and parallel to the first line of spaced facestock sheet second labels;
the facestock sheet including a weakened [[fold]] line;
the weakened line lying in a fold line;
the facestock sheet being constructed and adapted to be and capable of being bent back on the weakened fold line to thereby separate the liner sheet away from portions of the first labels whereby the portions of the first labels can be individually grasped ~~by a user~~ and the first labels individually peeled off of the liner sheet;
~~wherein~~ the weakened [[fold]] line ~~does not penetrate~~ not penetrating the liner sheet; and
~~wherein~~ the facestock sheet ~~includes~~ including at least one facestock non-label waste portion, the weakened [[fold]] line being in the facestock non-label waste portion and not on the first labels.

93. (Previously Presented) The construction of claim 92 wherein each of the labels has a burst configuration with alternating long and short points.

94. (Cancelled).

95. (Previously Presented) The construction of claim 92 wherein centerpoints of the first labels define a line and the fold line is spaced from and parallel to the line.

96. (Previously Presented) The construction of claim 92 wherein the liner sheet has a silicone coating, and a layer of adhesive is sandwiched between the facestock sheet and the silicone coating.

97. (Previously Presented) The construction of claim 19 further comprising adhesive coating the entireties of all bottom surfaces of the first label and of the second label.

Serial No. 09/954,621

PATENT

New Atty Docket No.: 67134-5040

98. (Previously Presented) The construction of claim 44 further comprising adhesive coating the entire bottom surface of the label including the label portion.
99. (Previously Presented) The construction of claim 44 wherein the first and second weakened line segments are both cut lines.
100. (Previously Presented) The construction of claim 50 further comprising adhesive coating the entire bottom surface of the label including the label portion.
101. (Previously Presented) The construction of claim 57 further comprising adhesive coating the entire bottom surface of the label including the label portion.
102. (Previously Presented) The construction of claim 65 further comprising adhesive coating the entire bottom surface of the label.
103. (Previously Presented) The construction of claim 65 wherein the first weakened line segment is in a non-label waste portion of the facestock sheet and the second weakened line segment is in a non-label waste portion of the facestock sheet.
104. (Previously Presented) The construction of claim 67 further comprising adhesive coating the entire bottom surface of the label.
105. (Previously Presented) The construction of claim 69 further comprising adhesive coating the entire bottom surfaces of the label.
106. (Previously Presented) The construction of claim 73 wherein a non-label waste matrix portion of the facestock sheet surrounds each of the labels, and the weakened fold line is in the non-label waste matrix portion.
107. (Previously Presented) The construction of claim 75 further comprising adhesive coating the entire bottom surfaces of all of the labels.
108. (Previously Presented) The construction of claim 84 further comprising adhesive coating the entire bottom surfaces of the first, second and third labels.

Serial No. 09/954,621

PATENT

New Atty Docket No.: 67134-5040

109. (Currently Amended) The construction of claim 84 further comprising a third weakened line ~~third~~ segment outside of, and extending at least substantially from the first label to the second label, a fourth weakened line ~~fourth~~ segment outside of, and extending at least substantially between the second and third labels, the ~~[[same]]~~ weakened fold line defines a first weakened fold line which passes through the first, second and third labels; the third and fourth weakened line segments defining a second weakened fold line which passes through the first, second and third labels; the first and second weakened fold lines being parallel to one another, spaced from one another, and both on the same side of the centerpoint line.

110. (Previously Presented) The construction of claim 92 further comprising adhesive coating the entire bottom surfaces of all of the first labels and all of the second labels.

111. (New) The construction of claim 19 wherein the die cut line is continuous with the at least one first cut line and the at least one second cut line.

112. (New) The construction of claim 44 wherein there are no weakened lines in the liner sheet contiguous with the first weakened line segment or with the second weakened line segment.

113. (New) The construction of claim 50 wherein an end of the first weakened segment closest to the label is spaced a distance therefrom by a short section of uncut material.

114. (New) The construction of claim 57 wherein there are no weakened lines in the liner sheet contiguous with the first, second third or fourth weakened line segments.

115. (New) The construction of claim 65 wherein there are no weakened lines in the liner sheet contiguous with the first weakened line segment or with the second weakened line segment.

Serial No. 09/954,621

PATENT
New Atty Docket No.: 67134-5040

116. (New) The construction of claim 67 wherein there are no weakened lines in the liner sheet contiguous with the first weakened line segment or with the second weakened line segment.

117. (New) The construction of claim 69 wherein there are no weakened lines in the liner sheet contiguous with the first weakened line segment or with the second weakened line segment, and the first and second weakened line segments are both elongate continuous die cut lines.

118. (New) The construction of claim 75 wherein there are no weakened lines in the liner sheet contiguous with the die cut line segments.

119. (New) The construction of claim 75 wherein the die cut line segments are spaced from adjacent ones of the labels by short sections of uncut material.

120. (New) The construction of claim 77 wherein the weakened fold line is an elongate continuous die cut line.

121. (New) The construction of claim 120 wherein there are no weakened lines in the liner sheet contiguous with the weakened fold line.

122. (New) The construction of claim 84 wherein there are no weakened lines in the liner sheet contiguous with the first weakened line segment or with the second weakened line segment.

123. (New) The construction of claim 89 wherein the liner sheet has no weakened lines which are contiguous with the weakened line segment.

124. (New) The construction of claim 92 wherein the weakened fold line is a cut line through the facestock sheet but not through any of the labels.

125. (New) A label sheet construction, comprising:
a liner sheet;
a facestock sheet adhered to the liner sheet;

Serial No. 09/954,621

PATENT

New Atty Docket No.: 67134-5040

at least one cut line through the facestock sheet but not the liner sheet to form a facestock sheet label releasably adhered to the liner sheet;

a weakened line segment in the facestock sheet, outside of the label, not penetrating the liner sheet, on a non-label portion of the facestock sheet and between the label and an adjacent edge of the facestock sheet;

the weakened line segment defining a weakened fold line of the construction;

the weakened fold line passing through the label; and

the construction being structured such that the facestock sheet can be bent back on the weakened fold line to separate the liner sheet away from a portion of the label so that the label portion can be grasped and the label can be peeled off of the liner sheet.

126. (New) The construction of claim 125 wherein the weakened line segment is an elongate continuous die cut line.

126. (New) The construction of claim 126 wherein the die cut line is continuous with the at least one cut line.

128. (New) The construction of claim 125 wherein the weakened line segment is perpendicular to an edge of the facestock sheet.

129. (New) The construction of claim 125 wherein there are no weakened lines in the liner sheet contiguous with the weakened line segment.

130. (New) The construction of claim 125 wherein the label is surrounded by a non-label portion of the facestock sheet.

131. (New) The construction of claim 125 wherein the facestock sheet includes a non-label edge frame, and the weakened line segment is in the frame.

132. (New) The construction of claim 125 wherein the facestock sheet includes a plurality of labels including the label, each of the labels being surrounded by non-label portions of the facestock sheet.

Serial No. 09/954,621

PATENT

New Atty Docket No.: 67134-5040

133. (New) The construction of claim 125 wherein the weakened line segment defines a first weakened line segment, and a second weakened line segment is in the facestock sheet and on the fold line, and the label is positioned between the first and second weakened line segments.